

## TECHNICAL DATA SHEET

DWR112Y/ZY

UL/ANSI White Conduit Pipe RSC (Rigid Steel Conduit) 1½ " Pipe



### Technical Specification

<b>Sub Category</b>	UL/ANSI
<b>Series</b>	White Conduit Pipe
<b>Sub Series</b>	RSC (Rigid Steel Conduit)
<b>Product Type</b>	Pipe
<b>Size (inch)</b>	1½
<b>Outside Diameter (mm)</b>	48.26
<b>Minimum Wall Thickness (mm)</b>	3.35
<b>Length (mm)</b>	3,025
<b>Normal Weight (Kg/pc)</b>	11.22
<b>Primary Bundle (pcs)</b>	3
<b>Master Bundle (pcs)</b>	75
<b>Standard Pack (pcs/Box)</b>	-
<b>Standard Pack (pcs/Box) Inner Box</b>	-
<b>Standard Pack (pcs/Box) Outer Box</b>	-
<b>Normal Wall Thickness (mm)</b>	-
<b>Certificate</b>	UL6 / ANSI C80.1
<b>Characteristics</b>	Hot-Dip Galvanized Outside and Epoxy Resin Inside

Disclaimer: All information contained here is given according to our specifications and best knowledge and can be changed without further notice.  
 This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.  
 It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.  
 Neither Panasonic Middle East and Africa FZE nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.